



- Super Strong Power
- **S** Driving Comfort
- Super High Load-bearing

JORDAN SANY Diesel Truck



Read E-brochure

SANY HEAVY TRUCK "JORDAN" VERSION

SUPER STRONG POWER

German power, maximum horsepower 520 horsepower, maximum torque 2550 Nm.

DRIVING COMFORT

The cab has high reliability and large driving space, high corrosion resistance and durability; flat floor body, stylish appearance, large driving space, avant-garde interior, good quietness, and high reliability.

SUPER HIGH LOAD-BEARING

For sand and gravel transportation, it is matched with 8+7-way double layer frame, 7.5-ton front axle, 13-ton wheel reduction rear axle, providing super strong load-bearing capacity.

PRODUCT TECHNICAL SPECIFICATION

Host Code			KQY100001025
	Drive Type		6×4
Basic Parameters	Length×Width ×Height(unladen) (mm)		6965×2545×3910
	Emission		Euro III
	Wheel Base (mm)		3300+1350
	Front Overhang/Rear Overhang (mm)		1515/800
	The Fifth-Wheel		90#
	Height of the Fifth-Wheel from Ground Without Load (mm)		1400
	Front Bumper Ground Clearance (mm)		460
	Minimum Ground Clearance (mm)		240
	Front Turning Radius (mm)		2300
	Rear Turning Radius (mm)		2200
	Curb Weight (kg)		10500
	Gross Vehicle Weight (kg)		25000
	Gross Combination Weight (kg)		80000
Frame Parameter	Section Heigth×Section Width× Frame Thickness (mm)		300×80×(8+7)
Engine	Туре		D13C3-520E0
	Rated Power (hp) / (rpm)		520/1900
	Max Torque (Nm)/ (rpm)		2550/1000-1400
Transmission	Туре		F12JZ26A-FHB400-QHG50C
	Number of Gears		Forward gear 12, reverse gear 2
	Ratios		1th gear ratio 12.26, 12th gear ratio 0.78
Brake System	Туре		EBS+ESC
Cab	Configuration Description		High roof, wide flat floor, Left-hand drive, 2 sleeper, middle-position bumper. Outside sun shield. Electric rearview mirror with heating function. Rear window, Adjustable Seat, AC, 7 Inches dashboard. 12 Inches central control screen. Electric window.
Axle	Front	Load Capacity (t)	7.5t
	Middle/Rear	Load Capacity (t)	13t/13t
		Ratio	4.266
Tyres	Model		Front: 385/65R22.5, Rear: 315/80R22.5
Suspension	Front /Rear		Front 3 leaf spring/rear 8 air suspension
Battery	Voltage (V)		24 (12×2)
	Battery Capacity (Ah)		220
Fuel	Туре		Aluminum fuel tank, with lockable cap
	Capacity		500L
Trailer Electrical Interface			15pin
Trailer Power Supply			24V
Optional Configurations			

Reminder:

Any change in the technical parameters and configuration due to product modification or upgrade may occur without prior notice. The machine in the picture may include additional equipment. This brochure is for reference only, and goods in kind shall prevail.

Copyright at SANY. No part of this brochure may be copied or used for any purpose without written approval from SANY. © Version 2025-08-08









