

SANY®

QUALITY CHANGES THE WORLD



 Strong Passing Ability

 Powerful Energy

 Reliability

MIDDLE EAST 6X6

SANY Diesel Truck



Read E-brochure

SANY HEAVY TRUCK "MIDDLE EAST 6X6" VERSION

STRONG PASSING ABILITY

6×6 All-Wheel-Drive, With optimal design High-position metal bumper, Height more than 800mm, improving off-road and passing ability.

POWERFUL ENERGY

Deutz D13 Engine, Max horsepower 565, better than other brands and better performance in different working conditions.

RELIABILITY

With mature and strong load bearing system, with 10T front axle and 16T rear axle, strengthened framework. Stable and reliable.

PRODUCT TECHNICAL SPECIFICATION

Host Code			KQY100001073		KQY100001079	
Basic Parameters	Length × Width × Height(unladen) (mm)		7965×2570×3970		7965×2570×3970	
	Emission		Euro V		Euro VI	
	Wheel base (mm)		4000+1450		4000+1450	
	Front overhang (mm) / Rear overhang (mm)		1680/835		1680/835	
	The Fifth-Wheel		90#		90#	
	Height of the fifth-wheel from ground without load (mm)		1615±20		1615±20	
	Front bumper ground clearance (mm)		800		800	
	Minimum Ground Clearance (mm)		400		400	
	Front Turning Radius (mm)		2400		2400	
	Rear Turning Radius (mm)		2400		2400	
	Curb weight (kg)		12800		12800	
	Gross Vehicle Weight (kg)		42000		42000	
	Gross Combination Weight (kg)		120000		120000	
	Frame Parameter	Section height×Section width×Frame thickness (mm)		300× (940-850) × (8+7) , Partial Three-Layer Strengthened Frame		300× (940-850) × (8+7) , Partial Three-Layer Strengthened Frame
Engine	Type		D13C5-565E2		D13C6-560E4	
	Rated Power (Hp) / (rpm)		565/1900		560/1900	
	Max Torque (Nm) / (rpm)		2580/1000-1500		2580/1000-1500	
Transmission	Type (AMT/MT)		C12JSDQXL260TA (MT)		C12JSDQXL260TA (MT)	
	Number of gears		Forward gear 12, reverse gear 2		Forward gear 12, reverse gear 2	
	Ratio		1th gear ratio 12.26, 12th gear ratio 0.78		1th gear ratio 12.26, 12th gear ratio 0.78	
Brake	Type		ABS		ABS	
Cab	Configuration description		Semi-high roof, wide flat floor , High-position metal bumper、 Outside sun shield、 Electric rearview mirror with heating function、 Rear window, Adjustable Seat, AC, 7 Inches dashboard、 12 Inches central control screen、 Electric window.		Semi-high roof, wide flat floor , High-position metal bumper、 Outside sun shield、 Electric rearview mirror with heating function、 Rear window, Adjustable Seat, AC, 7 Inches dashboard、 12 Inches central control screen、 Electric window.	
Axle	Front	Load capacity (t)	10		10	
	Middle/ Rear	Load capacity (t)	32		32	
		Ratios	6.733		6.733	
Tyres	Model		16.00R20		16.00R20	
Suspension	Front /Rear		Front 4 leaf spring/Rear 12 leaf spring		Front 4 leaf spring/Rear 12 leaf spring	
Battery	Voltage (v)		24 (12×2)		24 (12×2)	
	Battery capacity (Ah)		220		220	
Fuel	Type		Aluminum fuel tank, with lockable cap		Aluminum fuel tank, with lockable cap	
	Capacity		700L		700L	
Trailer electrical			7pin		7pin	
Trailer power supply			24V		24V	
Alternate configuration			Optional EBS		Optional EBS、 5.262rear axle ratio	

Reminder:
Any change in the technical parameters and configuration due to product modification or upgrade may occur without prior notice. The machine in the picture may include additional equipment. This brochure is for reference only, and goods in kind shall prevail.
Copyright at SANY. No part of this brochure may be copied or used for any purpose without written approval from SANY.
© Version 2025-08-05

