

High Safety

High Comfort

High Reliability

SANY TRUCK

RUSSIA 4X2
MODELS



<https://www.sanytruck.com/intl/>



@SANY TRUCK
Follow Us, Know More

SANY HEAVY TRUCK "RUSSIA 4X2" VERSION

HIGH SAFETY

Standard EBS, standard Lane departure Warning, front collision warning, 360 surround view, fatigue monitoring, safer transportation.

HIGH COMFORT

Sany Jiangshan high-roof cab, first-class large space, one-button start, steering-integrated shifter, more convenient and comfortable.

HIGH RELIABILITY

Million kilometers of vehicle durability verification, rust-proof, dustproof and waterproof to C5 standard, the vehicle is durable, the service life of more than one million kilometers.

PRODUCT TECHNICAL SPECIFICATION

Host Code			KQY100001063	KQY100001046
Basic Parameters	Length × Width × Height(unladen)(mm)		6065×2545×3910	6065×2545×3910
	Emission		Euro V	Euro V
	Wheel base (mm)		3750	3750
	Front overhang (mm)/ Rear overhang (mm)		1515/800	1515/800
	The Fifth-Wheel		50#	50#
	Height of the fifth-wheel from ground without load(mm)		1150	1150
	Front bumper ground clearance (mm)		375	375
	Minimum Ground Clearance (mm)		240	240
	Front Turning Radius(mm)		2040	2040
	Rear Turning Radius(mm)		1835	1835
	Curb weight (kg)		7575	7575
	Gross Vehicle Weight (kg)		19500	19500
	Gross Combination Weight (kg)		44000	44000
Frame Parameter	Section heighth×Section width×Frame thickness(mm)		300×(940-850)×8	300× (940-850) ×8
Engine	Type		D13C5-485E1	M12E5-470E0
	Rated Power (Hp) / (rpm)		485/1900	470/1800
	Max Torque (Nm)/ (rpm)		2350/1000-1400	2300/900-1400
Transmission	Type (AMT/MT)		F12JZ24+FHB400+QHG50C (AMT)	F12JZ24+QHG50C (AMT)
	Number of gears		Forward gear 12, reverse gear 2	Forward gear 12, reverse gear 2
	Ratios		1st gear ratio 15.70,12th gear ratio 1.00	1st gear ratio 15.70,12th gear ratio 1.00
Brake System	Type		EBS+ESC	EBS+ESC
Cab	Configuration description		High-roof flat floor,12.3-inch instrument, 12.1-inch central control touchscreen, electrically adjustable&electrically heating rearview mirror, Handheld wire-controlled lift system, multi-function steering wheel, Automatic headlights with Rain-Sensing wipers, Ventilated heated and massage driver's seat , Built-In Refrigerator, Independent Heating System, side + top shroud	High-roof flat floor,12.3-inch instrument, 12.1-inch central control touchscreen, electrically adjustable&electrically heating rearview mirror, Handheld wire-controlled lift system, multi-function steering wheel, Automatic headlights with Rain-Sensing wipers, Ventilated heated and massage driver's seat , Built-In Refrigerator, sleeper reading light,Independent Heating System, side + top shroud
Axle	Front	Load capacity (t)	7.5	7.5
	Middle/ Rear	Load capacity (t)	13	13
		Ratio	2.714	2.714
Tyres	Model		315/70R22.5	315/70R22.5
Suspension	Front /Rear		Front 3 leaf spring/rear 4 air suspension	Front 3 leaf spring/rear 4 air suspension
Battery	Voltage (V)		24	24
	Battery capacity (A.h)		2×220	2×220
Fuel	Type		Aluminum fuel tank, with lockable cap	Aluminum fuel tank, with lockable cap
	Capacity		600L+500L	600L+500L
Trailer electrical interface			15pin	15pin
Trailer power supply			24V	24V
Alternate configuration			Optional 2.846,3.364(Overdrive Transmission) rear axle ratios	Optional Retarder,Engine 490 HP