

Low Fuel Consumption

• High Adaptability

• High Security

SANY TRUCK

RUSSIA 6X2R
MODELS



<https://www.sanytruck.com/intl/>



@SANY TRUCK

Follow Us, Know More

SANY HEAVY TRUCK "RUSSIA 6X2R" VERSION

LOW FUEL CONSUMPTION

Rear axle can be lifted, reduce friction resistance when light load, transport more fuel-efficient; using the most advanced technology in Europe. Deutz engine + Bosch ECU, with intelligent torque control, shift smoothly, more than congeneric products fuel saving about 1%.

HIGH ADAPTABILITY

The whole car parts low temperature design, through the -45 °C low temperature and cold test; short wheelbase, adapt to more working conditions, turn around more convenient .

HIGH SECURITY

Standard EBS, double warning, 360 look around, fatigue monitoring, driving safer.



PRODUCT TECHNICAL SPECIFICATION

Host Code			KQY100001060
Basic Parameters	Length×Width ×Height(unladen)(mm)		6945×2545×3950
	Emission		Euro V
	Wheel base (mm)		3300+1350
	Front overhang/Rear overhang (mm)		1575/750
	The Fifth-Wheel		50#
	Height of the fifth-wheel from ground without load(mm)		1210
	Front bumper ground clearance (mm)		430
	Minimum Ground Clearance(mm)		240
	Front Turning Radius(mm)		2200
	Rear Turning Radius(mm)		2150
	Curb Weight (kg)		9150
	Gross Vehicle Weight (kg)		28500
	Gross Combination Weight (kg)		55000
Frame Parameter	Section heighth×Section width×Frame thickness(mm)		300×（940-850）×8, Partial Double-Layer Strengthened Frame
Engine	Type		D13C5-525E1
	Rated Power (hp) / （rpm）		525/1900
	Max Torque (Nm)/ （rpm）		2550/1000-1400
Transmission	Type		F12JZ26+FHB400+QHG50C（AMT）
	Number of gears		Forward gear 12, reverse gear 2
	Ratios		1th gear ratio 17.09, 12th gear ratio 1
Brake System	Type		EBS+ESC
Cab	Configuration description		High-roof flat floor, Left-hand drive, Wind deflector, 12.1-inch large screen, Full LCD instrument cluster, Upper and lower berths, Driver's air suspension seat, Warning lights, Electric heated mirrors, Electric air conditioning, Electric tilt cab, Multi-function steering wheel, Electric window lifts.
Axle	Front	Load capacity（t）	7.5
	Middle/ Rear	Load capacity（t）	13/8
		Ratio	3.083
Tyres	Model		385/65R22.5; 315/70R22.5
Suspension	Front /Rear		Front 3-leaf spring/Rear 8-air suspension
Battery	Voltage（V）		24（12×2）
	Battery capacity（Ah）		220
Fuel	Type		Aluminum fuel tank,with lockable cap
	Capacity		400L+300L
Trailer electrical interface			15pin
Trailer power supply			24V
Optional configurations			Speed ratio optional 2.846; Front tire optional 315/70R22.5