

High  
Reliability

Attractive  
Appearance

Low Energy  
Consumption

V2V  
Charging

High  
Standard

High Energy  
Efficiency

# SANY TRUCK

437kWh  
COMPOSITE VERSION



<https://www.sanytruck.com/intl/>



**@SANY TRUCK**  
Follow Us, Know More

## SANY ELECTRIC HEAVY TRUCK 6x4 437 kWh COMPOSITE VERSION

### HIGH RELIABILITY

Historical Attendance Rate > 95%, providing high efficient transportation service for our clients. 3 Years Market Validation + 2 Times Cold Region Test Calibration + 3-Round Annual Model Upgrading.

### ATTRACTIVE APPEARANCE

Passenger Car-Style Dual-color Soft-touch Dashboard, 12-inch LCD Instrument Cluster, Ultra-size Multi-Media Display, WIFI, Navigation System, Electronic Gear Shift.

### LOW ENERGY CONSUMPTION

Standard AMT Shift Lever Switch, Economy/Power Mode, Achieve Multi-gear Coasting Energy Regeneration

### V2V CHARGING

Charging Power 40kWh. Vehicle-to-Vehicle Charging and Discharging, More Convenient for Emergency Power Supply, Charging Efficiency Up to 94%.

### HIGH STANDARD

European Standard, Core Component have passed the stringent ECE certification, and the overall vehicle quality satisfy world-class standards.

### HIGH ENERGY EFFICIENCY

PTC Power Intelligent Adjustment, 5-level Electric Braking Adjustment, Electric Power Regeneration Rate  $\geq 36\%$ .

## PRODUCT TECHNICAL SPECIFICATION

Model			6x4 437 kWh COMPOSITE VERSION
Basic Parameters	Host Code		KEV123143619
	Driver's seat location (left/right)		Left hand drive
	Length×Width×Height (unladen)(mm)		7470×2545×3400
	Wheel base (mm)		3800+1350
	Front overhang /Rear overhang (mm)		1540/780
	The Fifth-Wheel		50# fifth-wheel
	Front distance of the fifth wheel (mm)		900
	The Height of the fifth-wheel (mm)		1285±20
	Minimum Ground Clearance (mm)		280
	Front Turning Radius (mm)		2150
	Rear Turning Radius (mm)		2050
	Curb weight (kg)		12000
	Technically Permissible Gross Combination Weight (kg)		80000
Frame Parameter	Section heigth×Section width×Frame thickness (mm)		300×80×(8+5)
Driving Motor	Type		High Performance Centre Drive Motor
	Rated Power (kW)/Rotation Speed (r/min)/Torque (N.m)		330/2300/1370
	Peak Power (kW)/Rotation Speed (r/min)/Torque(N.m)		480/3500/2800
Power Battery	Battery capacity (kWh)		437 kWh
	Energy supply method		600A dual-gun DC fast-charging/5min swapping
	Charging standard		China's Standard GB/T
	Charging Time		20%-80% ≤ 45min
Transmission	Type		4-speed AMT
	Number of gears		4-speed AMT + Coasting Switch
	Power take off		Spline, EZF700-007HC
Vehicle control unit	Type		Self-developed VCU
Axle	Front	Load capacity	7.5t
	Middle/Rear	Load capacity	13t/13t
		Ratio	5.262
Tyres	Type		12R22.5 front tire, 445/65R22.5 large single rear tire
Rim	Type		Aluminum
Suspension	Front /Rear		Front 3 Leaf Spring/Rear Air Suspension
Braking System	Type		ABS+ESC+Braking energy regeneration function
Trailer electrical interface			7 pin
Trailer power supply			24 V